

making **RF** the strongest link

NL5500

TELEMETRY APPLICATIONS

- Data Terminals
- Water Management
- Remote Data Loggers
- Oil & Gas Monitoring
- Irrigation Control Security Systems

MOBILE APPLICATIONS

- Database Access
- Computer Aided Dispatch
- Vehicle Tracking
- Asset Tracking
- Fleet Management

FEATURES

- Modem and Transceiver
- Synthesized VHF and UHF
- Narrow Band or Wideband
- Complete Programmable Features
- Compact Size: 3.0" L x 2.6" W x 1.4" H
- Powerful DSP - 288 MIPS
- Superior Radio Performance
- Serial Port - RS232
- CRC (For FEC use NL6000)

FREQUENCY RANGES

136-162 MHz VHF
148-174 MHz VHF
216-235 MHz VHF
400-420 MHz UHF
450-470 MHz UHF

HIGH PERFORMANCE DSP
TMS320VC5509 - 288 MIPS

Wireless Modem

Cost-Effective VHF/UHF Performance



PRODUCT OVERVIEW

The NL5500 Transceiver Series is a price/performance leader in licensed conventional radios in both the VHF and UHF frequency range. The capability for transparent and direct asynchronous communication offers real-time communication. The NL5500 is fully compatible with RF Neulink's NL6000. It will communicate and coexist with NL6000s, while providing excellent throughput and long range for multiple address systems. The NL5500 Transceiver Series is field configurable as a master station or remote radio. These units can operate as a half-duplex or simplex radios. The simplex mode facilitates peer-to-peer radio communications while using a carrier sense (CSMA) channel collision avoidance technique.

The NL5500 is ideal for any system where cost-effective performance, reliable data rates, and compact size are a requirement.

rfneulink
making **RF** the strongest link
Division of RF Industries

7610 Miramar Road, San Diego, CA 92126-4202
(800)233-1728 or (858)549-6340 Fax: (858)549-6349
Email: rwhite@rfneulink.com Website: www.rfneulink.com

SPECIFICATIONS

General	VHF	UHF
Frequency Range	136–174 MHz	400–470 MHz
Channel Spacing	12.5 or 25 kHz.....	12.5 or 25 kHz
Channel Increment.....	2.5 kHz.....	5/6.25 kHz
Operating Temperature.....	-30° to +60° C.....	-30° to +60° C
Operating Humidity.....	90% at 40° C non-condensing.....	90% at 40° C non-condensing
Frequency Stability (-30°to+60°C).....	1.5 PPM.....	1.5 PPM
12.5 kHz Channel Data Rate.....	12 kbps	12 kbps
25 kHz Channel Data Rate.....	22 kbps	22 kbps
User Interface		
Data Rate of RS-232 Serial Port	1200 – 38,400 bps configurable	
Connectors.....	9 pin D type as DCE	
Addressing	Selective ID, Group & Broadcast	
Supply Voltage		
Input Voltage Range	11 – 16 VDC with internal regulator	
NL6000 Max Current Drain.....	≤2.5 A	≤2.5 A
Transmitter		
Operating Bandwidth.....	26 MHz.....	20 MHz
RF Output Power.....	1–6 watts.....	1–6 Watts
Duty Cycle.....	5 to 100% depending on power and temperature	
RF Load Impedance	50 ohms	50 Ohms
Transmitter Attack Time.....	≤15 ms	≤15 ms
Spurious & Harmonics.....	≤-20 dbm	≤-20 dbm
FM Hum & Noise		
12.5 kHz channel operation.....	≥40 db.....	≥40 db
25 kHz channel operation.....	≥45 db.....	≥45 db
Current Drain		
1 watt.....	≤1.0 A	≤1.0 A
6 watt.....	≤2.4 A	≤2.4 A
Receiver		
Operating Bandwidth.....	26 MHz.....	20 MHz
Sensitivity (12 db SINAD w/de-emphasis).....	≤0.28 uV.....	≤0.28 uV
Adjacent Channel Selectivity		
+/- 12.5 w/narrow IF.....	≥60 db.....	≥60 db
+/- 25 w/wide IF	≥70 db.....	≥70 db
Spurious & Image Rejection.....	≥70 db.....	≥70 db
Intermodulation Rejection	≥70 db.....	≥70 db
FM Hum & Noise		
12.5 kHz channel operation.....	≥40 db.....	≥40 db
25 kHz channel operation.....	≥45 db.....	≥45 db
Conducted Spurious.....	≤-57 dbm	≤-57 dbm
Receive Attack Time	≤15 ms	≤15 ms
RSSI Squelch Attack Time	≤15 ms	≤15 ms
Receive Current Drain	≤80 mA.....	≤75 mA

RF Neulink reserves the right to change specifications of this product at any time without notice and without obligation to notify any person of such changes.
For outside operation of radio-modem products a NEMA 4 enclosure is recommended.

ORDERING INFO

To contact RF Neulink's Sales Team for details, call toll-free 1-800-233-1728 or email rwhite@rfneulink.com.

rfneulink
making **RF** the strongest link
Division of RF Industries

7610 Miramar Road
San Diego, CA 92126-4202
(800)233-1728 or (858)549-6340
Fax: (858)549-6349
Email: rwhite@rfneulink.com
Website: www.rfneulink.com

WHO IS RF NEULINK?



RF Neulink has been manufacturing radio link equipment for 30 years. Our line of transmitter and receiver units for point-to-point communications, paging excitors, radio data and control products reflect our experience in this marketplace.

Our publicly held parent company, RF Industries (NASDAQ symbol RFIL), provides a well capitalized base for continued future growth and product development. RF Neulink's customers include Fortune 500 companies, municipalities, government agencies, educational and health institutions, utilities, small companies, casinos, irrigation companies, armed forces here and abroad, and many others that need or want reliable, state-of-the-art, cost-effective communications links.